



Drycleaner Containment Structure Certification

Drycleaning Restoration Trust Fund

Bureau of Land and Waste Management
2600 Bull Street, Columbia, SC 29201-1708

(See Instructions on Page 3)

Type or Print All Entries

SCDHEC USE ONLY

A. Registrant Information

1.

Date Received:

Registrant Name (Owner/Partnership/Corporate Charter Registered with DOR)

App. Completed: Y N -- / /

2.

()

Project Number:

Application Contact Person

Telephone

3.

Company Mailing Address

City

State

Zip Code

B. Facility Information – (Business Name)

4.

Facility Street Address or Specific Physical Location

City

Zip Code

5.

()

Facility Contact Person

Title/Position

Telephone

6.

Did the Facility operate before November 24, 2004?

Yes, See Section D – Containment **A** Guidelines.

No, See Section D – Containment **B** Guidelines.

C. Applicant Signature and Notarization

I hereby attest that the referenced facility meets or exceeds the containment requirements outlined in 7a or 7b above. In addition, all information contained in this form is accurate.

7.

Signature of Company Executive (Application Contact Person)

Title

SWORN to before me this _____ Day of _____

NOTARY PUBLIC FOR SOUTH CAROLINA

My commission expires: _____

IMPRINT NOTARY SEAL HERE

D. Containment Guidelines (Please check applicable guideline.)

Containment A Guidelines – (Operating before November 24, 2004)

Facility must install dikes or other containment structures around each machine or item of equipment in which drycleaning solvents are used and around an area in which solvents or waste containing solvents are stored. The containment must meet the following criteria:

- (1) the dikes or containment structures must be capable of containing one-third of the capacity of the total tank capacity of each machine;
- (2) dikes or containment structures around areas used for *storage* of solvents or waste containing solvents must be capable of containing one hundred percent of the volume of the largest container stored or retained in the containment structure;
- (3) all diked containment areas must be sealed or otherwise made impervious to the drycleaning solvents in use at the facility, including floor surfaces, floor drains, floor joints, and inner dike walls;
- (4) to the extent practicable, an owner of a drycleaning facility or person shall seal or otherwise render impervious those portions of all floor surfaces upon which any drycleaning solvents may leak, spill, or otherwise be released;
- (5) containment devices must provide for the temporary containment of accidental spills or leaks until appropriate response actions are taken by the owner/operator to abate the source of the spill and remove the product from all areas on which the product has accumulated; and
- (6) materials used in constructing the containment structure or sealing the floors must be capable of withstanding permeation by drycleaning solvents in use at the facility for not less than seventy-two hours.

Containment B Guidelines – (Operating after November 24, 2004)

Facility must install dikes or other containment structures around each machine or item of equipment in which drycleaning solvents are used and around an area in which solvents or waste containing solvents are stored. The containment must meet the following criteria:

- (1) a rigid and impermeable containment vessel capable of containing one hundred percent of the volume of the largest single tank in the machine or piece of equipment or one-third of the capacity of the total tank capacity of each machine whichever is greater;
- (2) dikes or containment structures around areas used for *storage* of solvents or waste containing solvents must be capable of containing one hundred percent of the volume of the largest container stored or retained in the containment structure; Dikes or containment structures must be installed before delivery of any drycleaning solvents to the facility.
- (3) all diked containment areas must be sealed or otherwise made impervious to the drycleaning solvents in use at the facility, including floor surfaces, floor drains, floor joints, and inner dike walls;
- (4) to the extent practicable, an owner of a drycleaning facility or person shall seal or otherwise render impervious those portions of all floor surfaces upon which any drycleaning solvents may leak, spill, or otherwise be released;
- (5) containment devices must provide for the temporary containment of accidental spills or leaks until appropriate response actions are taken by the owner/operator to abate the source of the spill and remove the product from all areas on which the product has accumulated; and
- (6) materials used in constructing the containment structure or sealing the floors must be capable of withstanding permeation by drycleaning solvents in use at the facility for not less than seventy-two hours.

Instructions for Containment Structure Certification Form

Purpose: This form is used to certify that containment structures are in place at all operating drycleaning facilities.

Definitions:

Drycleaning Solvent means any cleaning liquid, formula or solution designed to minimize swelling of fabric fibers and containing less than fifty-one percent of water by volume.

Drycleaning Facility means a location where drycleaning solvents are used, or have been used in the past, for cleaning of clothing and/or other fabrics for members of the public. Also commonly known as a “Wet Site”.

Dry-drop Facility means any location (store, etc.) used for pick-up or delivery of items that are drycleaned at a different location. Dry-drop facilities may have been used as Wet Site locations in the past.

Wet Site means the drycleaning facility and includes the building where the drycleaning machine is actually located along with any support functions (pressing, spotting, customer counter, etc.).

Wholesale Supply Facility means a location that is used, or has been used in the past, as a warehouse or distribution point for drycleaning solvents to Drycleaning Facilities.

A. Registrant Information

1. The Registrant Name should be the same as the “Owner/Partnership/Corporate Charter Name” filed with the Department of Revenue (DOR) on DOR form L-2093. If the Company Name has changed since the initial registration with DOR, the most recent company name registered with DOR should be entered on this application.
2. The Application Contact Person is be the Registrant’s owner, partner, corporate executive or other fiduciary agent with responsibility for ensuring the accuracy of the information submitted on the application.
3. Enter the complete mailing address of the contact person listed above.

B. Facility Information

4. The specific street address of the facility should be listed. If there is no specific address, the site location should be referenced to the nearest readily identifiable intersection (e.g., “east side of Oak Street, 550 feet south of the intersection of Oak and Pine Streets”).
5. The Facility Contact Person is a manager or other reliable employee that will normally be at the facility during daytime business hours. Enter the Facility Contact Person’s position or title and a daytime telephone number.
6. *Self explanatory.*

C. Applicant Signature and Notarization

7. A company executive or the Applicant Contact Person (from line 2) must sign the application form. Notary Publics commissioned within the State of South Carolina are not required to imprint their seal. Out of State Notaries (or equivalent) must imprint their seal.

The completed form should be submitted to:

**SCDHEC
Drycleaning Restoration Trust Fund
Bureau of Land and Waste Management,
2600 Bull Street Columbia, SC 29201-1708**